

1. A display control apparatus comprising:
 - a video memory for storing color data, which is displayed dots, palette data for use in conversion of the color data into displayed dots;
 - representing addresses of the color data and the palette data;
 - a first video memory controller for reading the color data from the video memory in accordance with the address data, so that the color data is outputted to the color palette memory;
 - a second video memory controller for reading the palette data from the color palette memory in accordance with the address data, so that the palette data is outputted to the color palette memory;
 - conversion on the color palette memory in accordance with the palette data;
 - an output circuit for outputting either the color data from the video memory or converted color data output from the color palette memory;
 - wherein if present address data designating the color data is inputted, the first video memory controller reads the color data from the video memory in accordance with the present address data;
 - wherein if present address data designating the palette data is inputted, the second video memory controller reads the palette data from the color palette memory in accordance with the present address data;
 - wherein if the present address data designating the palette data is inputted, the second video memory controller does not write the present palette data to the color palette memory;

- [illegible]

- Sub 02



Sub 22

4. A display control apparatus comprising:
- a video memory for storing display data that contain header data, palette data and bitmap data in connection with a plurality of planes which are combined together to form one frame of picture, wherein the header data contain a color palette pointer and a color palette replacer instruction with respect to each of the planes;
 - a color palette memory for storing color palettes with respect to the plurality of planes;
 - a video memory controller for reading the palette data and the bitmap data from the video memory in accordance with addresses designated by the header data; and
 - a color palette replacer signal generator for generating a color palette replacer signal based on the header data so as to make determination whether to replace content of the color palette with respect to each of the planes,
- wherein if the color palette replacer instruction designates color palette replacement, the video memory controller unconditionally replaces previous palette data with present palette data on the color palette memory, while if the color palette replacer instruction does not designate color palette replacement, the video memory controller replaces the previous palette data with the present palette data on the color palette memory only when a present color palette pointer designating the present

palette data differs from a previous color palette pointer designating the previous palette data.

5. A display control apparatus according to claim 4 wherein the header data contain a bitmap data format representing a format of the bitmap data with respect to each of the planes, so that the bitmap data are converted to RGB color data on the color palette memory in response to the bitmap data format.

add
a3

add
B1

1. **Содержание:** 1. Введение. 2. Описание объекта. 3. Анализ состояния. 4. Методы исследования. 5. Результаты. 6. Заключение.